



IO Fact Sheet

Standard Features

- Built in microprocessor controlling all operations and providing volumetric dosages for coffee brewing.
- Four programmable doses per group, with manual brewing button.
- Two stainless steel steam wands and one manual hot water tap.
- Automatic water re-fill and built in volumetric pump as standard.

Barista Down lights



Raised groups



Color Options:

PEARLY WHITE



	SAE 1 ●	SAE 2 ●
Total Wattage	2,330/2,930 watt	4,800 watt
Heating Element	2,000/2600 watt	4,400 watt
Boiler	6 ltr	10.5 ltr
Net Weight	126 lbs	159 lbs
Approx Ship Weight	200 lbs	230 lbs
Measurements W x D x H	23.2" x 22 x 22.8	31.5" x 22" x 22.8"
Power	110 volt/ 19.4 amps  NEMA 5-20P	220 volt/21.4 amps  Nema L6-30

Water Requirements

- 3/8" dedicated cold water line with shut off valve and compression fitting.
- Water hardness cannot exceed 3gpg or 50ppm.
- Water softener must be installed if it exceeds the limits.
- Minimum incoming water flow rate of 35 GPH and the maximum line pressure of 70 PSI/5 BAR

Drain Requirements

Open gravity drain of minimum 1.25 inch within 4 feet of the machine

